

**PAT-NO:** JP408239458A  
**DOCUMENT-IDENTIFIER:** JP 08239458 A  
**TITLE:** POLYESTER POLYOL AND ITS USE AS A BINDER IN  
TWO COMPONENT POLYURETHANE COATING COMPOSITION  
**PUBN-DATE:** September 17, 1996

**INVENTOR-INFORMATION:**

NAME	COUNTRY
WAMPRECHT, CHRISTIAN	N/A
SONNTAG, MICHAEL	N/A

**ASSIGNEE-INFORMATION:**

NAME	COUNTRY
BAYER AG	N/A

**APPL-NO:** JP08016989  
**APPL-DATE:** January 8, 1996

**INT-CL (IPC):** C08G063/12 , B05D007/14 , C08G018/42 , C08G018/68 , C08G063/52 , C09D175/14

**ABSTRACT:**

**PROBLEM TO BE SOLVED:** To obtain a novel two-component polyurethane coating composition which meets industrial requirements such as no yellowing on exposure to UV light of a short wavelength and which is most suitable for re-finishing of automotive vehicles and lacquer coating of heavy motor vehicles.

**SOLUTION:** A polyester polyol having a hydroxyl value of 60 to 400 comprises an esterified product of a) an alcohol component containing at least one aliphatic or alicyclic alcohol having at least three hydroxyl groups and 3 to 8 carbon atoms, and b) a carboxylic acid component containing itaconic acid, maleic acid, an anhydride thereof and/or fumaric acid [provided that at least 10 mol.% of either component a) or component b) consists of an aliphatic or alicyclic saturated or unsaturated monoalcohol or monocarboxylic acid having 1 to 18 carbon atoms].

**COPYRIGHT:** (C)1996,JPO